



PRINTING & ARTWORK SPECIFICATIONS GUIDE

Platforms:

- Macintosh (Preferred)
- PC (Accepted)

Dies and Die Lines:

- See die line reference file under Information Files" within your Account page. The die line design template is also available on the products page.

Accepted Programs/File Formats:

- Adobe Illustrator CC 2018 (Preferred)
- Adobe Photoshop CC 2018
- Adobe Acrobat PDF (high resolution)
- Adobe InDesign CC 2018 (Accepted, not preferred, please include print quality PDF)

NOTE: Non-vector formats can be sent for reference only. Colors fonts and layout may not be accurate

File Information:

Uploads: Please include all placed images/links (i.e. EPS, TIFF, PSD, JPG, etc.) used for the design embedded into your file. Placed images must be at least 300 dpi resolution for print quality purposes. PNG, GIFF and other low/web resolution images are not acceptable for print. Whenever possible, please keep the file sizes below 50MB for easier use.

Fonts: Please include all required fonts with your files or convert the text to outlines/paths on the file for best results. Please include printer font if using postscript fonts. Minimum point size for positive type is 5pt. The minimum point size for reverse type is 8pt Bold.

Rule Thickness: Minimum positive rule (line) weight is .007 in. or .5 pt. Minimum reverse rule (line) weight is .01389 in. or 1pt.

Colors: When assigning a spot color to graphics or text, please indicate the Pantone color call-out. Please clearly specify colors such as White, Varnish, Clear or Metallic Substrate when applicable for clarity. CMYK is acceptable with screens of 100% to 1% minimum if possible. All gradients should fade to 1% and should not fade to 0% in any color for best results.

Print Tolerances: Please include die line. Please provide 1/8" total bleed outside of die line (1/16" on all sides) where applicable. Please leave 1/8" total inner tolerance between die line and graphic elements (1/16" on all sides) to allow for movement on press.

Bar Code: Recommended minimum UPC bar code magnification is 80%. Bar codes printed smaller than 80% magnification may have difficulty scanning in some applications.

Providing Artwork:

Upload Online: An .ai file uploaded through the shop is the Preferred method of file transfer. When providing art files via the product shop, please email a PDF file of the artwork and a copy of your invoice to info@liquidtherapyinnovations.com for reference.

Email: When providing art files as an email attachment please include a PDF file of the artwork for reference. We cannot accept encrypted compressed files via email.

NOTE: Final Artwork Layout Revision must be approved by the customer prior to receiving commitment to production launch and production scheduling timeline

If you have any additional questions please contact us.

info@liquidtherapyinnovations.com

(203)-998-1149



PRINTING & ARTWORK SPECIFICATIONS GUIDE

Flexo – Character Standard

Specification:

Print to Print Register $\pm 1/64$ " ($\pm 1/32$ " for 1.5% of order)

- Unless the aesthetic acceptability of graphics has not been compromised

Print to Die Register $\pm 1/32$ " ($\pm 1/16$ " for 1.5% of order)

- Printing on the adhesive requires $3/8$ " no copy area to die cut with $\pm 3/16$ " position tolerance

Barcode reading of "C" (ISO based grade) or better

- or as required by customer

Liner width $\pm 1/32$ "

Label edge to liner edge $\pm 1/32$ " ($- 3/64$ " for 1.5% of order)

Label count per roll $\pm 1\%$

Splices per roll – 3 or less

- 3 or less for 90% of the order or as required by customer

Missing labels per roll – 5 or less

- no consecutive missing labels or as required by customer

Visual match to a PMS or custom color

- or as required by customer

Order Quantity shipped $\pm 10\%$

- or as required by customer

Digital – Character Standard

Specification:

Print to Print Register $\pm .005$ "

- Unless the aesthetic acceptability of graphics has not been compromised

Print to Die Register $\pm 1/32$ " ($\pm 1/16$ " for 1.5% of order)

Barcode reading of "C" (ISO based grade) or better

- or as required by customer

Liner width $\pm 1/32$ "

Label edge to liner edge $\pm 1/32$ " ($- 3/64$ " for 1.5% of order)

Label count per roll $\pm 1\%$

Splices per roll – 3 or less

- 3 or less for 90% of the order or as required by customer

Missing labels per roll – 5 or less

- no consecutive missing labels or as required by customer

Visual match to a PMS or custom color

- or as required by customer

Order Quantity shipped $\pm 10\%$

- or as required by customer

If you have any additional questions please contact us.

info@liquidtherapyinnovations.com

(203)-998-1149